



Product Specifications for E57906-WT

Job Name:	Job Type:
Quantity:	Comments:



**E57906-WT**  
**CounterMax MX-L 30" LED Under Cabinet Light**  
 Uses MXInterLink2 accessories. Click [here](#) for a complete list of compatible accessories.

**Finish**  
White

**Glass/Shade**  
Clear

**Product Category**  
Under Cabinet Kit

**Lamping**

Number of Bulb(s)	6
Light Type	LED
Bulb Type	LED
Max Bulb Wattage	1
Max Fixture Wattage	6
Rated Life	±50,000 Hours
Rated Lumens	±480
Color Temp	±3,000 K
Bulb(s) Included	Integrated
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

**Measurements**

Width	2.00"
Height	1.00"
Length	30.00"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	1.50 lb(s)
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

**Shipping**

Carton Weight	1.75 lb(s)
Carton Width	3.38"
Carton Height	2.25"
Carton Length	36.38"
Carton Cubic Feet	N/A
Master Pack	6
Master Pack Weight	11.50 lb(s)
Master Pack Width	7.88"
Master Pack Height	7.75"
Master Pack Length	36.88"
Master Cubic Feet	N/A
UPS Shippable	Yes

**Certification**

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

**Other**

UPC Code	845094027522
Material	Aluminum

**Equivalents**

Incandescent Watts	43.64
Fluorescent Watts	9.6

ET2 Contemporary Lighting and all designs, logos and images © 2015 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.