

| Product Specifications for E92051-38 | |
|--------------------------------------|-----------|
| Job Name: | Job Type: |
| | |
| Quantity: | Comments |
| | |

E92051-38

Carte 1-Light Pendant

Finish Bronze

Glass/Shade Blue Ripple

Other

UPC Code

Material

Product Category

Single Pendant

Lamping Number of Bulb(s) **Light Type** Incandescent **Bulb Type** MB Max Bulb Wattage 100 **Max Fixture Wattage** 100 **Rated Life** ±2,500 Hours **Rated Lumens** ±1,150 Color Temp ±2,700 K Bulb(s) Included No Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Standard Dimmer **Dimmable**

Measurements Width 5.00" Height 13.00" Length 5.00" Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A **HCO** N/A Min Overall Height 24.00" Max Overall Height 60.00" Hanging Weight N/A **Height Adjustable** N/A Slope 120° Chain Length N/A Wire Length 120.00" **Canopy Width** N/A Canopy Height N/A Canopy Length N/A

| Shipping | |
|--------------------|-----|
| Carton Weight | N/A |
| Carton Width | N/A |
| Carton Height | N/A |
| Carton Length | N/A |
| Carton Cubic Feet | N/A |
| Master Pack | 1 |
| Master Pack Weight | N/A |
| Master Pack Width | N/A |
| Master Pack Height | N/A |
| Master Pack Length | N/A |
| Master Cubic Feet | N/A |
| UPS Shippable | Yes |
| | |
| | |

Certification

Safety Rating Dry **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No

Equivalents

845094020363

Incandescent Watts N/A Fluorescent Watts N/A

ET2 Contemporary Lighting and all designs, logos and images © 2015 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.