<b>=</b>  2	Contemporary Lighting™
-------------	---------------------------

Product Specifications for E92143-14				
Job Name:	Job Type:			
	21			
Quantity:	Comments			

	E	£ ()
III		

## E92143-14 Carte 3-Light Pendant

Finish Satin Nickel

Lamping

Number of Bulb(s) **Light Type** Incandescent **Bulb Type** MB Max Bulb Wattage 100 Max Fixture Wattage 300 **Rated Life** ±2,500 Hours **Rated Lumens** ±3,450 Color Temp ±2,700 K Bulb(s) Included No Light Up/Down **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No Dimmable Standard

**Glass/Shade** Amber Ripple

Other

**UPC** Code

Material

Measurements

## Width 5.50" Height 11.50" Length 24.50" Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A **HCO** N/A Min Overall Height 24.00" **Max Overall Height** 60.00" Hanging Weight 11.64 lb(s) **Height Adjustable** N/A Slope 120° Chain Length N/A Wire Length 120.00" **Canopy Width** N/A Canopy Height N/A Canopy Length N/A

**Product Category** Linear Pendant

Lincar i Chaan

	Shipping	
"	Carton Weight	N/A
"	Carton Width	N/A
"	Carton Height	N/A
٨	Carton Length	N/A
١	Carton Cubic Feet	N/A
٨	Master Pack	1
١	Master Pack Weight	N/A
"	Master Pack Width	N/A
"	Master Pack Height	N/A
)	Master Pack Length	N/A
١	Master Cubic Feet	N/A
0	UPS Shippable	Yes
١		
"		

## Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Equivalents

845094024781

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2016 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.