





PRODUCT DESCRIPTION

1.25"⊏

*max overall height

Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. The continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.

MEASUREMENTS

DIMENSION : 38.5" L x 1.5" W x 1.25" H

MAX OAH : 121" OAH

CANOPY : 5" W x 1" H x 5" L

HANGING WEIGHT : 3.03 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 2,250 Rated (1,800 Del.)

BULB : 1 x 28W LED PCB Integrated , 28W Total

BULB INCLUDED : (Integrated)

DIMMABLE: 3-in-1: Triac, ELV, 0-10V

CRI : 90 CRI

COLOR_TEMP : Select 30/35/40K

FINISHES OPTION

Black (BK)

Satin Aluminum (SA)

White (WT)

GLASS

Frosted 90

MATERIAL

Acrylic, Aluminum

RATINGS

cETLus Dry Location



ADDITIONAL

RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



121"

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com