ALUMILUX PATH LED / PATHWAY

E41367


- ETL, CETL IP65
- LED 3000K, CRI 80+
- Wet Location

Job Name			
Job Type			
Quantity			
Comments			



PRODUCT DESCRIPTION

Provide safe and functional lighting along your paths by adding spot lighting and bollards. These machined aluminum products enhance the architectural elements of your home by using techniques like grazing and uplighting. Whether you choose to accentuate an object of interest or extend your living space, this collection has the sleek and slim profile to blend seamlessly into your pathways.



MEASUREMENT

DIMENSIONS : 6"W x 23.5"H WIRE LENGTH : 36" HANGING WEIGHT : 1.8 Lb

LAMPING

INPUT VOLTAGE : 12V

LUMENS : 210 Rated (203 Delivered)
BULB : (1) 3W PCB LED (Integrated)

DIMMABLE : No CRI : 80+ BEAM SPREAD : 360 COLOR TEMPERATURE: 3000K

FINISHES OPTIONS:

Bronze (BZ)
Satin Aluminum (SA)



MATERIAL:

Aluminum

RATINGS:

ETL cETL IP65 Wet Location Title 24 (For Outdoor)









ADDITIONAL:

RATED LIFE: 35,000 Hours

OPERATING TEMP: -20° C (-4°), 40°C (104°F)

PHOTOMETRIC: Report Found Online

PCB LED Included

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTERS)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336