


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 67.24 lm/W			
MODEL	3000K	I _{max} (cd)	887.9	S/MH(C0/180)	1.20
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.15
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	2249.9	η UP,DN(C0-180)	1.1,48.7
NOMINAL FLUX(lm)	2249.89	CIE CLASS	DIRECT	η UP,DN(C180-360)	1.1,49.1
LAMPS INSIDE	1	η up(%)	2.1	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	97.9	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2022-09-16

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity: 65.0%
Test Distance: 7.480m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum,lamp
5	880.3	881.6	881.9	881.6					0- 5	21.14	21.14	0.94,0.94
10	863.0	861.9	866.1	861.9					5- 10	62.41	83.55	3.71,3.71
15	835.6	828.5	840.1	828.5					10- 15	100.6	184.2	8.19,8.19
20	798.9	784.2	804.6	784.2					15- 20	134.0	318.2	14.1,14.1
25	753.9	732.0	760.7	732.0					20- 25	161.2	479.4	21.3,21.3
30	702.2	674.0	709.7	674.0					25- 30	181.5	660.9	29.4,29.4
35	645.4	612.5	653.2	612.5					30- 35	194.4	855.3	38,38
40	584.5	549.8	592.6	549.8					35- 40	200.1	1055	46.9,46.9
45	520.8	486.6	528.9	486.6					40- 45	198.8	1254	55.7,55.7
50	455.7	423.6	463.6	423.6					45- 50	191.3	1446	64.2,64.2
55	389.7	361.6	397.3	361.6					50- 55	178.0	1623	72.2,72.2
60	323.8	300.4	330.7	300.4					55- 60	159.6	1783	79.3,79.3
65	258.0	240.3	264.6	240.3					60- 65	137.1	1920	85.3,85.3
70	192.9	180.4	198.8	180.4					65- 70	110.9	2031	90.3,90.3
75	129.9	124.2	135.1	124.2					70- 75	82.52	2114	93.9,93.9
80	71.63	72.43	75.80	72.43					75- 80	53.58	2167	96.3,96.3
85	26.21	29.56	28.97	29.56					80- 85	26.98	2194	97.5,97.5
90	5.268	5.704	5.237	5.704					85- 90	7.926	2202	97.9,97.9
95	5.631	5.286	5.513	5.286					90- 95	2.892	2205	98,98
100	6.046	5.629	5.921	5.629					95-100	3.051	2208	98.1,98.1
105	6.481	6.060	6.355	6.060					100-105	3.222	2211	98.3,98.3
110	6.911	6.513	6.793	6.513					105-110	3.376	2215	98.4,98.4
115	7.319	6.978	7.212	6.978					110-115	3.494	2218	98.6,98.6
120	7.704	7.427	7.597	7.427					115-120	3.565	2222	98.7,98.7
125	8.070	7.850	7.971	7.850					120-125	3.576	2225	98.9,98.9
130	8.398	8.254	8.306	8.254					125-130	3.531	2229	99.1,99.1
135	8.706	8.608	8.623	8.608					130-135	3.423	2232	99.2,99.2
140	9.008	8.948	8.935	8.948					135-140	3.257	2235	99.4,99.4
145	9.335	9.287	9.248	9.287					140-145	3.045	2239	99.5,99.5
150	9.667	9.618	9.571	9.618					145-150	2.784	2241	99.6,99.6
155	9.979	9.934	9.895	9.934					150-155	2.474	2244	99.7,99.7
160	10.30	10.20	10.21	10.20					155-160	2.114	2246	99.8,99.8
165	10.61	10.43	10.50	10.43					160-165	1.707	2248	99.9,99.9
170	10.83	10.58	10.73	10.58					165-170	1.256	2249	100,100
175	10.99	10.76	10.90	10.76					170-175	0.7696	2250	100,100
180	11.07	10.82	11.00	10.82					175-180	0.2603	2250	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
 Humidity:65.0%
 Test Distance:7.480m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.04	.00	.96	1.02	.98	.94	.97	.94	.91	.93	.90	.88	.89	.87	.85	.83
2.0	.91	.85	.79	.89	.83	.78	.85	.80	.76	.82	.77	.74	.78	.75	.72	.70
3.0	.80	.72	.66	.79	.71	.65	.75	.69	.64	.72	.67	.63	.70	.65	.61	.59
4.0	.71	.63	.56	.70	.62	.56	.67	.60	.55	.65	.59	.54	.62	.57	.53	.51
5.0	.64	.55	.49	.63	.55	.48	.60	.53	.48	.58	.52	.47	.56	.51	.46	.44
6.0	.58	.49	.43	.57	.49	.43	.55	.47	.42	.53	.46	.41	.51	.45	.41	.39
7.0	.53	.44	.38	.52	.44	.38	.50	.43	.37	.48	.42	.37	.47	.41	.36	.35
8.0	.48	.40	.34	.47	.39	.34	.46	.39	.33	.44	.38	.33	.43	.37	.33	.31
9.0	.44	.36	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.40	.34	.30	.28
10.0	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.37	.31	.27	.25



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.291
 Humidity: 65.0%
 Test Distance: 7.480m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm								
NAME: 48黑色寸扩散板 35W				TYPE:			WEIGHT:	
SPEC.:				DIM.:			SERIAL No.:1	
MFR.: EVERFINE				SUR.:			PROTECTION ANGLE:	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.296	.169	.053	.289	.165	.052	.274	.157	.050	.261	.151	.048	.249	.144	.047	
2.0	.280	.154	.047	.273	.151	.046	.261	.145	.045	.249	.140	.044	.238	.135	.042	
3.0	.260	.139	.041	.254	.136	.041	.243	.132	.040	.233	.127	.039	.223	.123	.038	
4.0	.241	.125	.037	.236	.123	.036	.226	.120	.036	.216	.116	.035	.208	.113	.034	
5.0	.223	.114	.033	.219	.112	.033	.210	.109	.032	.201	.106	.032	.194	.103	.031	
6.0	.208	.104	.030	.203	.103	.030	.195	.100	.029	.188	.098	.029	.181	.095	.028	
7.0	.194	.096	.027	.190	.095	.027	.183	.092	.027	.176	.090	.026	.170	.088	.026	
8.0	.181	.089	.025	.178	.088	.025	.171	.086	.024	.165	.084	.024	.159	.082	.024	
9.0	.170	.082	.023	.167	.081	.023	.161	.080	.023	.156	.078	.022	.150	.076	.022	
10.0	.160	.077	.021	.157	.076	.021	.152	.074	.021	.147	.073	.021	.142	.072	.021	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.207	.207	.207	.177	.177	.177	.121	.121	.121	.069	.069	.069	.022	.022	.022	
1.0	.196	.173	.152	.167	.148	.131	.115	.102	.090	.066	.059	.053	.021	.019	.017	
2.0	.187	.148	.116	.160	.128	.100	.110	.088	.070	.063	.051	.041	.020	.017	.013	
3.0	.179	.131	.092	.154	.113	.080	.105	.078	.056	.061	.046	.033	.020	.015	.011	
4.0	.171	.117	.076	.147	.101	.066	.101	.071	.047	.059	.041	.028	.019	.013	.009	
5.0	.164	.107	.065	.141	.093	.056	.097	.065	.040	.056	.038	.024	.018	.012	.008	
6.0	.157	.099	.057	.135	.085	.049	.093	.060	.035	.054	.035	.021	.017	.011	.007	
7.0	.150	.092	.051	.129	.079	.044	.089	.056	.031	.052	.033	.019	.017	.011	.006	
8.0	.144	.086	.046	.124	.074	.040	.086	.052	.028	.050	.031	.017	.016	.010	.006	
9.0	.138	.081	.042	.119	.070	.037	.082	.049	.026	.048	.029	.016	.016	.010	.005	
10.0	.132	.077	.040	.114	.067	.035	.079	.047	.025	.046	.028	.015	.015	.009	.005	

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-09-16

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity:65.0%
Test Distance:7.480m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm										
NAME: 48黑色寸扩散板 35W					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:1		
MFR.: EVERFINE					SUR.:			PROTECTION ANGLE:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.3	20.7	19.5	20.9	21.2	19.0	20.4	19.3	20.6	20.9
3H	20.6	22.0	21.0	22.2	22.5	20.3	21.7	20.6	21.9	22.2
4H	21.2	22.4	21.5	22.7	23.0	20.8	22.1	21.2	22.4	22.7
6H	21.5	22.7	21.8	23.0	23.3	21.2	22.4	21.6	22.7	23.0
8H	21.6	22.7	21.9	23.0	23.4	21.3	22.5	21.7	22.8	23.1
12H	21.6	22.7	22.0	23.0	23.4	21.3	22.5	21.7	22.8	23.1
4H 2H	19.8	21.0	20.1	21.3	21.6	19.5	20.8	19.9	21.1	21.4
3H	21.3	22.4	21.7	22.8	23.1	21.1	22.2	21.5	22.5	22.9
4H	22.0	23.0	22.4	23.3	23.7	21.7	22.7	22.1	23.1	23.5
6H	22.4	23.3	22.8	23.7	24.1	22.2	23.1	22.6	23.5	23.9
8H	22.5	23.4	23.0	23.8	24.2	22.3	23.2	22.8	23.6	24.0
12H	22.6	23.4	23.1	23.8	24.2	22.4	23.2	22.9	23.6	24.1
8H 4H	22.2	23.0	22.6	23.4	23.8	22.0	22.8	22.4	23.2	23.6
6H	22.7	23.4	23.2	23.9	24.3	22.6	23.2	23.0	23.7	24.2
8H	22.9	23.5	23.4	24.0	24.5	22.8	23.4	23.3	23.8	24.3
12H	23.1	23.6	23.6	24.1	24.6	22.9	23.4	23.4	23.9	24.5
12H 4H	22.2	22.9	22.6	23.4	23.8	22.0	22.7	22.4	23.1	23.6
6H	22.8	23.4	23.3	23.9	24.3	22.6	23.2	23.1	23.7	24.2
8H	23.0	23.5	23.5	24.0	24.5	22.8	23.4	23.4	23.9	24.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.3 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117 Corrected 2250 lm Total Lamp Luminous Flux.(8log(F/F0) = 2.8)

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-09-16

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity:65.0%
Test Distance:7.480m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	59	48	41	58	47	41	57	47	40	34
0.80	69	57	50	68	57	50	66	56	50	43
1.00	77	66	59	76	66	59	73	67	58	51
1.25	84	74	67	82	73	66	80	71	65	58
1.50	89	79	72	87	78	72	84	76	71	63
2.00	95	87	81	93	86	80	90	83	78	70
2.50	99	92	86	97	90	85	93	87	83	74
3.00	102	96	90	100	94	89	96	91	87	78
4.00	106	101	96	104	99	95	99	95	92	82
5.00	109	104	100	106	102	98	101	98	95	85
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity: 65.0%
Test Distance: 7.480m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:

Conical surface Flux(90deg):

1254.2 lm

%lum = 55.7%


%lamp = 55.7%

Conical surface Flux(120deg):

1783.1 lm

%lum = 79.3%

%lamp = 79.3%



5%	44.39
10%	88.79
15%	133.2
20%	177.6
25%	222.0
30%	266.4
35%	310.8
40%	355.2
45%	399.5
50%	443.9
55%	488.3
60%	532.7
65%	577.1
70%	621.5
75%	665.9
80%	710.3
85%	754.7
90%	799.1
95%	843.5

1. AVG=879.0, MIN=869.1
2. AVG=876.0, MIN=856.5
3. AVG=871.9, MIN=839.8

Imax:887.9 (H0.0, V-0.5)
(At:C=90.0, Gamma=0.0)


UNIT: cd

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-09-16

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity:65.0%
Test Distance:7.480m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.291
 Humidity: 65.0%
 Test Distance: 7.480m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 γ Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity:65.0%
Test Distance:7.480m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:


AvgL	cd/m2
L_0~180 (65) av	6184
L_0~180 (75) av	5120
L_0~180 (85) av	3165
L_90~270 (65) av	5685
L_90~270 (75) av	4797
L_90~270 (85) av	3392
L_45 (65) av	5877
L_45 (75) av	4925
L_45 (85) av	3317

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
 Humidity:65.0%
 Test Distance:7.480m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2022-09-16

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity: 65.0%
Test Distance: 7.480m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.0V I:0.2803A P:33.46W PF:0.9944 Lamp Flux:2249.89x1 lm		
NAME: 48黑色寸扩散板 35W	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	PROTECTION ANGLE:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	90	180	270															
0	887	888	887	888															
5	880	882	882	882															
10	863	862	866	862															
15	836	829	840	829															
20	799	784	805	784															
25	754	732	761	732															
30	702	674	710	674															
35	645	613	653	613															
40	584	550	593	550															
45	521	487	529	487															
50	456	424	464	424															
55	390	362	397	362															
60	324	300	331	300															
65	258	240	265	240															
70	193	180	199	180															
75	130	124	135	124															
80	71.6	72.4	75.8	72.4															
85	26.2	29.6	29.0	29.6															
90	5.27	5.70	5.24	5.70															
95	5.63	5.29	5.51	5.29															
100	6.05	5.63	5.92	5.63															
105	6.48	6.06	6.36	6.06															
110	6.91	6.51	6.79	6.51															
115	7.32	6.98	7.21	6.98															
120	7.70	7.43	7.60	7.43															
125	8.07	7.85	7.97	7.85															
130	8.40	8.25	8.31	8.25															
135	8.71	8.61	8.62	8.61															
140	9.01	8.95	8.93	8.95															
145	9.33	9.29	9.25	9.29															
150	9.67	9.62	9.57	9.62															
155	9.98	9.93	9.90	9.93															
160	10.3	10.2	10.2	10.2															
165	10.6	10.4	10.5	10.4															
170	10.8	10.6	10.7	10.6															
175	11.0	10.8	10.9	10.8															
180	11.1	10.8	11.0	10.8															

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2022-09-16

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.291
Humidity:65.0%
Test Distance:7.480m [K=1.0000]
Remarks: