


## LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 4.56 lm/W
MODEL	EDS2835	I <sub>max</sub> (cd)	49.74	S/MH(C0/180)	2.12	
NOMINAL POWER(W)	11	LOR(%)	4.4	S/MH(C90/270)	1.31	
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	57.485	h UP,DN(C0-180)	0.2,1.9	
NOMINAL FLUX(lm)	1320	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.2,2.0	
LAMPS INSIDE	1	h up(%)	0.4	CIBSE SHR NOM	1.50	
TEST VOLTAGE(V)	120.6	h down(%)	3.9	CIBSE SHR MAX	1.55	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM(UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
5	9.377	9.275	9.250	9.340	9.482	9.343	9.242	9.265	0- 5	0.2226	0.2226	0.39,0.02
10	9.759	9.390	9.165	9.525	10.000	9.551	9.149	9.351	5- 10	0.6719	0.8945	1.56,0.07
15	10.47	9.694	9.080	9.890	10.85	9.959	9.055	9.615	10- 15	1.144	2.038	3.55,0.15
20	11.42	10.16	8.813	10.42	11.93	10.55	8.784	10.03	15- 20	1.653	3.692	6.42,0.28
25	12.50	10.71	8.545	10.98	13.11	11.18	8.512	10.52	20- 25	2.201	5.892	10.2,0.45
30	13.53	11.35	8.278	11.63	14.20	11.89	8.241	11.12	25- 30	2.785	8.677	15.1,0.66
35	14.37	12.04	7.843	12.30	15.05	12.62	7.793	11.78	30- 35	3.385	12.06	21,0.91
40	14.91	12.69	7.408	12.94	15.58	13.28	7.346	12.40	35- 40	3.967	16.03	27.9,1.21
45	15.12	13.18	6.972	13.45	15.76	13.76	6.898	12.91	40- 45	4.504	20.53	35.7,1.56
50	14.70	13.48	6.380	13.75	15.28	14.01	6.278	13.22	45- 50	4.953	25.49	44.3,1.93
55	13.79	13.56	5.789	13.82	14.38	14.00	5.658	13.31	50- 55	5.243	30.73	53.5,2.33
60	12.88	12.93	5.197	13.24	13.44	13.18	5.038	12.70	55- 60	5.378	36.11	62.8,2.74
65	0	12.04	4.336	12.41	0	12.21	4.200	11.79	60- 65	4.659	40.76	70.9,3.09
70	0	10.43	3.475	10.92	0	10.78	3.361	10.29	65- 70	3.705	44.47	77.4,3.37
75	0	7.903	2.615	8.649	0	8.822	2.523	8.073	70- 75	2.950	47.42	82.5,3.59
80	0	5.329	1.754	6.353	0	6.882	1.684	5.820	75- 80	2.125	49.55	86.2,3.75
85	0	2.729	0.8932	4.044	0	4.960	0.8459	3.547	80- 85	1.462	51.01	88.7,3.86
90	0	0.1189	0.0326	1.716	0	3.041	0.0074	1.271	85- 90	0.7675	51.78	90.1,3.92
95	0	0.1193	0.0399	1.340	0	2.351	0.0161	0.9996	90- 95	0.7200	52.49	91.3,3.98
100	0	0.1190	0.0473	0.9619	0	1.665	0.0248	0.7331	95-100	1.236	53.73	93.5,4.07
105	0	0.1157	0.0547	0.5992	0	1.003	0.0334	0.4691	100-105	1.484	55.21	96.1,4.18
110	0	0.0993	0.0621	0.2738	0	0.3864	0.0421	0.2026	105-110	1.561	56.78	98.8,4.3
115	0	0.0885	0.0694	0.1364	0	0.1161	0.0508	0.0881	110-115	0.3648	57.14	99.4,4.33
120	0.1536	0.0972	0.0768	0.1247	0.1536	0.1088	0.0594	0.0944	115-120	0.0524	57.19	99.5,4.33
125	0.1164	0.1036	0.0817	0.1170	0.1536	0.1043	0.0537	0.1011	120-125	0.0488	57.24	99.6,4.34
130	0.1139	0.1049	0.0867	0.1196	0.1560	0.1087	0.0479	0.0948	125-130	0.0442	57.29	99.7,4.34
135	0.1139	0.0964	0.0916	0.1220	0.1560	0.1068	0.0421	0.0788	130-135	0.0400	57.33	99.7,4.34
140	0.0941	0.0834	0.0834	0.1184	0.1610	0.1099	0.0471	0.0699	135-140	0.0359	57.36	99.8,4.35
145	0.0842	0.0841	0.0751	0.1064	0.1536	0.1002	0.0520	0.0701	140-145	0.0312	57.39	99.8,4.35
150	0.0768	0.0842	0.0669	0.0875	0.1362	0.0894	0.0570	0.0750	145-150	0.0262	57.42	99.9,4.35
155	0.0643	0.0855	0.0694	0.0819	0.1214	0.0827	0.0636	0.0830	150-155	0.0212	57.44	99.9,4.35
160	0.0545	0.0832	0.0718	0.0717	0.1065	0.0773	0.0702	0.0862	155-160	0.0166	57.46	100,4.35
165	0.0545	0.0733	0.0743	0.0672	0.0917	0.0800	0.0768	0.0799	160-165	0.0126	57.47	100,4.35
170	0.0520	0.0638	0.0669	0.0628	0.0867	0.0819	0.0776	0.0754	165-170	0.0086	57.48	100,4.35
175	0.0520	0.0573	0.0594	0.0564	0.0817	0.0790	0.0784	0.0768	170-175	0.0050	57.48	100,4.35
180	0.0520	0.0520	0.0520	0.0520	0.0793	0.0793	0.0793	0.0793	175-180	0.0016	57.48	100,4.35
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31


g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature:30DEG  
 Operators:HCZ  
 Test Date:2017-10-31

g Range: 0 - 180DEG  
 g Interval: 0.5DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
 Humidity:65.0%  
 Test Distance:6.172m [K=1.0000]  
 Remarks:

# EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## WEC AND CCEC

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

rcc	80%	70%	50%	30%	10%	0
rw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
rfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)					
0.0						
1.0	.016 .009 .003	.015 .009 .003	.014 .008 .003	.014 .008 .003	.013 .007 .002	
2.0	.014 .008 .002	.014 .008 .002	.013 .007 .002	.012 .007 .002	.012 .007 .002	
3.0	.013 .007 .002	.013 .007 .002	.012 .006 .002	.011 .006 .002	.011 .006 .002	
4.0	.012 .006 .002	.012 .006 .002	.011 .006 .002	.010 .006 .002	.010 .005 .002	
5.0	.011 .006 .002	.011 .005 .002	.010 .005 .002	.009 .005 .001	.009 .005 .001	
6.0	.010 .005 .001	.010 .005 .001	.009 .005 .001	.009 .005 .001	.008 .004 .001	
7.0	.009 .005 .001	.009 .004 .001	.009 .004 .001	.008 .004 .001	.008 .004 .001	
8.0	.009 .004 .001	.008 .004 .001	.008 .004 .001	.008 .004 .001	.007 .004 .001	
9.0	.008 .004 .001	.008 .004 .001	.007 .004 .001	.007 .004 .001	.007 .003 .001	
10.0	.007 .004 .001	.007 .004 .001	.007 .003 .001	.007 .003 .001	.006 .003 .001	

rcc	80%	70%	50%	30%	10%	0
rw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
rfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)					
0.0	.012 .012 .012	.010 .010 .010	.007 .007 .007	.004 .004 .004	.001 .001 .001	
1.0	.011 .010 .009	.010 .009 .008	.007 .006 .005	.004 .003 .003	.001 .001 .001	
2.0	.011 .009 .007	.009 .008 .006	.006 .005 .004	.004 .003 .003	.001 .001 .001	
3.0	.011 .008 .006	.009 .007 .006	.006 .005 .004	.004 .003 .002	.001 .001 .001	
4.0	.010 .008 .006	.009 .007 .005	.006 .005 .004	.004 .003 .002	.001 .001 .001	
5.0	.010 .007 .005	.009 .006 .005	.006 .004 .003	.003 .003 .002	.001 .001 .001	
6.0	.010 .007 .005	.008 .006 .004	.006 .004 .003	.003 .003 .002	.001 .001 .001	
7.0	.010 .007 .005	.008 .006 .004	.006 .004 .003	.003 .002 .002	.001 .001 .001	
8.0	.009 .006 .005	.008 .006 .004	.005 .004 .003	.003 .002 .002	.001 .001 .001	
9.0	.009 .006 .004	.008 .005 .004	.005 .004 .003	.003 .002 .002	.001 .001 .001	
10.0	.009 .006 .004	.007 .005 .004	.005 .004 .003	.003 .002 .002	.001 .001 .001	

C Range: 0 - 360DEG  
 C Interval: 5.0DEG  
 Test Speed: HIGH  
 Temperature:30DEG  
 Operators:HCZ  
 Test Date:2017-10-31

g Range: 0 - 180DEG  
 g Interval: 0.5DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
 Humidity:65.0%  
 Test Distance:6.172m [K=1.0000]  
 Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

Uncorrected UGR Table

NAME: E41292-BZ						TYPE:					WEIGHT:				
DIM.:						SPEC.:					SERIAL No.:171031002				
MFR.: Maxim Lighting						SUR.:					PROTECTION ANGLE:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3					
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3					
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2					
Room dimensions						Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.5	14.1	13.0	14.5	14.9	10.4	11.9	10.8	12.3	12.8					
3H	12.6	14.0	13.0	14.4	14.8	12.0	13.4	12.4	13.8	14.2					
4H	12.4	13.8	12.9	14.2	14.7	12.5	13.8	12.9	14.3	14.7					
6H	12.3	13.5	12.8	14.0	14.5	12.9	14.1	13.3	14.6	15.1					
8H	12.2	13.4	12.7	13.9	14.4	13.0	14.2	13.5	14.6	15.2					
12H	12.2	13.3	12.7	13.8	14.3	13.0	14.2	13.5	14.7	15.2					
4H 2H	13.5	14.9	14.0	15.3	15.8	12.3	13.6	12.8	14.1	14.5					
3H	14.8	15.9	15.3	16.4	16.9	14.2	15.4	14.7	15.8	16.4					
4H	14.8	15.9	15.3	16.4	16.9	14.9	16.0	15.5	16.5	17.1					
6H	14.7	15.6	15.2	16.1	16.7	15.4	16.4	16.0	16.9	17.5					
8H	14.6	15.5	15.2	16.0	16.6	15.6	16.5	16.2	17.0	17.6					
12H	14.6	15.4	15.1	15.9	16.5	15.7	16.5	16.3	17.1	17.7					
8H 4H	15.8	16.7	16.3	17.2	17.8	15.8	16.7	16.4	17.3	17.9					
6H	16.2	16.9	16.8	17.5	18.1	16.7	17.4	17.3	18.0	18.6					
8H	16.2	16.8	16.8	17.4	18.1	17.0	17.6	17.6	18.2	18.9					
12H	16.1	16.7	16.8	17.3	18.0	17.2	17.8	17.8	18.4	19.1					
12H 4H	15.9	16.7	16.4	17.2	17.9	15.9	16.7	16.5	17.3	17.9					
6H	16.4	17.1	17.1	17.7	18.4	16.9	17.6	17.5	18.1	18.8					
8H	16.7	17.2	17.3	17.9	18.5	17.3	17.9	17.9	18.5	19.2					
Variations with the observer position at spacings:															
S = 1.0H	+ 0.4 / - 0.3					+ 0.1 / - 0.1									
1.5H	+ 0.7 / - 0.5					+ 0.3 / - 0.3									
2.0H	+ 0.6 / - 1.1					+ 0.8 / - 0.7									

CIE Pub.117 Corrected 1320 lm Total Lamp Luminous Flux.(8log(F/F0) = 1.0)

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## UTILIZATION FACTORS TABLE

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	2	1	1	2	1	1	2	1	1	1
0.80	2	2	2	2	2	2	2	2	1	1
1.00	3	2	2	3	2	2	3	2	2	2
1.25	3	3	2	3	3	2	3	3	2	2
1.50	3	3	3	3	3	3	3	3	2	2
2.00	4	3	3	4	3	3	3	3	3	2
2.50	4	4	3	4	3	3	4	3	3	3
3.00	4	4	3	4	4	3	4	4	3	3
4.00	4	4	4	4	4	4	4	4	4	3
5.00	4	4	4	4	4	4	4	4	4	3
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004					Suspended			SHRNM = 1.25		

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

```
g Range: 0 - 180DEG
g Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.275
Humidity:65.0%
Test Distance:6.172m [K=1.0000]
Remarks:
```

## ISOCANDELA DIAGRAM

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:




C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

## AAI Figure

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:



**Note:**The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.


C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:



## ISOLUX DIAGRAM


NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 30DEG  
Operators: HCZ  
Test Date: 2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity: 65.0%  
Test Distance: 6.172m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 30DEG  
Operators: HCZ  
Test Date: 2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity: 65.0%  
Test Distance: 6.172m [K=1.0000]  
Remarks:

## EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
0	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34
5	9.38	9.37	9.36	9.35	9.34	9.33	9.31	9.30	9.29	9.27	9.26	9.25	9.25	9.24	9.24	9.24	9.24	9.25	9.25
10	9.76	9.74	9.72	9.69	9.65	9.61	9.56	9.50	9.45	9.39	9.34	9.29	9.24	9.21	9.18	9.16	9.16	9.16	9.17
15	10.5	10.4	10.4	10.3	10.3	10.2	10.1	9.94	9.82	9.69	9.57	9.45	9.34	9.24	9.16	9.11	9.08	9.07	9.08
20	11.4	11.4	11.3	11.2	11.1	11.0	10.8	10.6	10.4	10.2	9.92	9.68	9.46	9.25	9.07	8.93	8.85	8.81	8.81
25	12.5	12.5	12.4	12.3	12.1	11.9	11.7	11.4	11.1	10.7	10.3	9.97	9.62	9.29	9.01	8.78	8.63	8.55	8.55
30	13.5	13.5	13.4	13.3	13.1	12.9	12.6	12.2	11.8	11.4	10.9	10.4	9.88	9.42	9.00	8.66	8.42	8.29	8.28
35	14.4	14.3	14.3	14.1	14.0	13.7	13.4	13.0	12.6	12.0	11.5	10.8	10.2	9.57	8.98	8.48	8.10	7.89	7.84
40	14.9	14.9	14.8	14.7	14.6	14.3	14.0	13.7	13.2	12.7	12.1	11.3	10.6	9.76	8.99	8.31	7.79	7.48	7.41
45	15.1	15.1	15.1	15.0	14.9	14.7	14.4	14.1	13.7	13.2	12.6	11.8	10.9	10.00	9.05	8.19	7.50	7.09	6.97
50	14.7	14.7	14.7	14.8	14.7	14.6	14.5	14.2	13.9	13.5	12.9	12.2	11.3	10.3	9.22	8.14	7.21	6.59	6.38
55	13.8	13.8	13.9	13.9	13.9	13.9	13.9	13.8	13.8	13.6	13.0	12.4	11.7	10.7	9.47	8.16	6.95	6.10	5.79
60	12.9	12.9	13.0	12.9	13.0	13.0	13.0	13.1	13.0	12.9	12.6	12.4	11.8	11.0	9.72	8.22	6.72	5.62	5.20
65	0.00	0.00	0.00	0.00	12.0	12.0	12.1	12.0	12.0	12.0	12.0	11.9	11.3	10.2	8.79	7.24	5.78	4.74	4.34
70	0.00	0.00	0.00	0.00	0.00	10.7	10.7	10.9	10.9	10.4	9.97	9.59	9.19	8.32	7.23	5.96	4.73	3.84	3.48
75	0.00	0.00	0.00	0.00	0.00	0.00	8.98	8.58	8.25	7.90	7.55	7.25	6.98	6.37	5.56	4.59	3.63	2.93	2.61
80	0.00	0.00	0.00	0.00	0.00	0.00	6.10	5.76	5.55	5.33	5.09	4.89	4.72	4.34	3.80	3.15	2.49	2.00	1.75
85	0.00	0.00	0.00	0.00	0.00	0.00	3.12	2.94	2.84	2.73	2.61	2.51	2.43	2.25	1.98	1.66	1.33	1.07	0.89
90	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.12	0.12	0.12	0.12	0.13	0.14	0.14	0.14	0.15	0.15	0.13	0.03
95	0.00	0.00	0.00	0.00	0.00	0.00	14.9	14.4	1.03	0.12	0.11	0.12	0.13	0.13	0.13	0.14	0.13	0.12	0.04
100	0.00	0.00	0.00	0.00	0.00	0.00	30.3	25.9	0.71	0.12	0.11	0.11	0.12	0.12	0.12	0.12	0.12	0.11	0.05
105	0.00	0.00	0.00	0.00	0.00	0.00	46.6	24.7	0.18	0.12	0.10	0.10	0.10	0.10	0.10	0.11	0.11	0.10	0.05
110	0.00	0.00	0.00	0.00	0.00	13.9	29.2	6.18	0.15	0.10	0.09	0.09	0.09	0.09	0.10	0.10	0.10	0.09	0.06
115	0.00	0.00	0.00	0.00	0.39	0.16	3.07	0.16	0.12	0.09	0.08	0.08	0.08	0.08	0.09	0.09	0.09	0.09	0.07
120	0.15	0.15	0.15	0.14	0.12	0.12	0.13	0.12	0.11	0.10	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.08	0.08
125	0.12	0.12	0.12	0.11	0.10	0.10	0.11	0.11	0.11	0.10	0.11	0.11	0.10	0.10	0.09	0.09	0.08	0.08	0.08
130	0.11	0.11	0.11	0.11	0.10	0.10	0.10	0.10	0.10	0.10	0.11	0.11	0.11	0.11	0.10	0.09	0.09	0.09	0.09
135	0.11	0.11	0.11	0.11	0.11	0.10	0.10	0.09	0.09	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.09	0.09
140	0.09	0.10	0.10	0.11	0.11	0.11	0.10	0.09	0.09	0.08	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.08	0.08
145	0.08	0.09	0.10	0.10	0.11	0.11	0.10	0.10	0.09	0.08	0.08	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.08
150	0.08	0.08	0.09	0.10	0.10	0.11	0.10	0.10	0.09	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07
155	0.06	0.07	0.07	0.08	0.08	0.09	0.09	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.07
160	0.05	0.06	0.06	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.09	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.07
165	0.05	0.06	0.06	0.06	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
170	0.05	0.05	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.07	0.07	0.07	0.07	0.07
175	0.05	0.05	0.05	0.05	0.05	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06
180	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

Table--2

UNIT: cd

C(DEG) g (DEG)	95	100	105	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185
0	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34
5	9.25	9.25	9.26	9.27	9.27	9.29	9.30	9.32	9.34	9.36	9.38	9.40	9.42	9.43	9.45	9.46	9.47	9.48	9.47
10	9.17	9.18	9.20	9.23	9.27	9.33	9.39	9.46	9.52	9.60	9.67	9.74	9.80	9.86	9.91	9.95	9.98	10.00	9.98
15	9.08	9.11	9.16	9.24	9.34	9.46	9.60	9.74	9.89	10.0	10.2	10.3	10.5	10.6	10.7	10.8	10.8	10.9	10.8
20	8.82	8.88	8.98	9.14	9.35	9.59	9.86	10.1	10.4	10.7	10.9	11.2	11.4	11.5	11.7	11.8	11.9	11.9	11.9
25	8.56	8.65	8.82	9.07	9.38	9.75	10.1	10.6	11.0	11.4	11.8	12.1	12.4	12.6	12.8	13.0	13.1	13.1	13.1
30	8.30	8.42	8.67	9.03	9.47	9.98	10.5	11.1	11.6	12.1	12.6	13.0	13.4	13.7	13.9	14.0	14.1	14.2	14.2
35	7.88	8.08	8.45	8.97	9.59	10.3	11.0	11.7	12.3	12.9	13.4	13.9	14.2	14.5	14.7	14.9	15.0	15.0	15.0
40	7.46	7.74	8.26	8.95	9.75	10.6	11.5	12.2	12.9	13.5	14.1	14.5	14.8	15.1	15.3	15.4	15.5	15.6	15.5
45	7.05	7.42	8.09	8.97	9.97	11.0	11.9	12.8	13.4	14.0	14.5	14.9	15.1	15.4	15.5	15.6	15.7	15.8	15.7
50	6.49	7.02	7.93	9.06	10.2	11.3	12.3	13.1	13.8	14.2	14.6	14.9	15.1	15.1	15.2	15.2	15.2	15.3	15.2
55	5.93	6.64	7.82	9.21	10.5	11.7	12.6	13.2	13.8	14.1	14.2	14.3	14.4	14.3	14.3	14.3	14.3	14.4	14.3
60	5.39	6.28	7.75	9.37	10.8	11.8	12.5	12.9	13.2	13.4	13.4	13.4	13.4	13.5	13.4	13.4	13.4	13.4	13.4
65	4.53	5.39	6.83	8.49	10.0	11.3	12.1	12.3	12.4	12.4	12.4	12.4	12.4	12.3	0.00	0.00	0.00	0.00	0.00
70	3.65	4.41	5.64	7.03	8.32	9.36	9.97	10.4	10.9	11.4	11.2	10.9	10.9	0.00	0.00	0.00	0.00	0.00	0.00
75	2.77	3.38	4.35	5.45	6.48	7.33	7.79	8.22	8.65	9.03	9.09	9.16	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80	1.88	2.32	2.99	3.78	4.56	5.21	5.60	5.99	6.35	6.65	6.71	6.87	0.00	0.00	0.00	0.00	0.00	0.00	0.00
85	0.99	1.22	1.58	2.05	2.58	3.06	3.40	3.72	4.04	4.29	4.43	4.62	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90	0.09	0.12	0.15	0.29	0.56	0.88	1.18	1.44	1.72	1.96	2.19	2.42	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95	0.09	0.12	0.14	0.25	0.47	0.73	0.96	1.15	1.34	1.51	1.82	2.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.08	0.11	0.13	0.21	0.38	0.57	0.73	0.86	0.96	1.05	1.03	28.8	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105	0.08	0.10	0.12	0.18	0.29	0.41	0.51	0.57	0.60	0.61	4.66	35.7	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.08	0.10	0.11	0.14	0.21	0.27	0.30	0.31	0.27	0.19	0.38	13.2	12.5	0.00	0.00	0.00	0.00	0.00	0.00
115	0.08	0.09	0.10	0.12	0.14	0.14	0.12	0.12	0.14	0.14	0.16	0.49	0.18	0.21	0.00	0.00	0.00	0.00	0.00
120	0.08	0.08	0.09	0.10	0.11	0.11	0.11	0.12	0.12	0.13	0.12	0.13	0.14	0.16	0.15	0.13	0.13	0.15	0.16
125	0.08	0.08	0.09	0.09	0.10	0.10	0.11	0.11	0.12	0.12	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.15	0.16
130	0.08	0.08	0.08	0.08	0.09	0.09	0.10	0.12	0.12	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.12	0.16	0.16
135	0.08	0.08	0.08	0.08	0.08	0.09	0.10	0.11	0.12	0.13	0.13	0.13	0.13	0.13	0.13	0.12	0.12	0.16	0.15
140	0.07	0.08	0.08	0.08	0.09	0.09	0.10	0.11	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.16	0.16
145	0.07	0.08	0.08	0.09	0.09	0.10	0.10	0.10	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.11	0.15	0.15
150	0.07	0.07	0.08	0.08	0.08	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.09	0.10	0.10	0.10	0.14	0.13
155	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.09	0.09	0.09	0.12	0.12
160	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.11	0.10
165	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.09	0.09
170	0.07	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.09	0.09
175	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.05	0.08	0.08
180	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.08	0.08

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

## EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

Table--3

UNIT: cd

C(DEG) g (DEG)	190	195	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280
0	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34
5	9.46	9.45	9.44	9.42	9.40	9.38	9.36	9.34	9.32	9.30	9.29	9.27	9.26	9.25	9.25	9.24	9.24	9.24	9.24
10	9.96	9.92	9.88	9.82	9.76	9.69	9.62	9.55	9.48	9.41	9.34	9.29	9.24	9.20	9.17	9.15	9.15	9.14	9.14
15	10.8	10.7	10.6	10.5	10.4	10.3	10.1	9.96	9.80	9.65	9.51	9.38	9.26	9.17	9.11	9.07	9.06	9.05	9.05
20	11.8	11.8	11.6	11.5	11.3	11.0	10.8	10.5	10.3	9.97	9.69	9.44	9.21	9.03	8.89	8.81	8.78	8.78	8.79
25	13.0	12.9	12.7	12.5	12.3	12.0	11.6	11.2	10.8	10.3	9.92	9.53	9.19	8.90	8.69	8.56	8.51	8.50	8.54
30	14.1	14.0	13.8	13.5	13.2	12.8	12.4	11.9	11.4	10.8	10.2	9.70	9.21	8.81	8.49	8.31	8.24	8.23	8.30
35	14.9	14.8	14.7	14.4	14.1	13.7	13.2	12.6	12.0	11.3	10.6	9.90	9.23	8.65	8.19	7.90	7.79	7.80	7.94
40	15.5	15.4	15.2	15.0	14.7	14.3	13.8	13.3	12.6	11.9	11.0	10.2	9.30	8.53	7.91	7.51	7.35	7.36	7.57
45	15.7	15.6	15.4	15.2	15.0	14.7	14.3	13.8	13.1	12.4	11.5	10.5	9.43	8.45	7.65	7.12	6.90	6.93	7.22
50	15.2	15.2	15.1	15.1	15.0	14.7	14.4	14.0	13.5	12.8	11.9	10.8	9.63	8.42	7.35	6.59	6.28	6.34	6.82
55	14.3	14.3	14.3	14.3	14.2	14.2	14.1	14.0	13.4	12.9	12.1	11.1	9.87	8.44	7.07	6.07	5.66	5.77	6.44
60	13.4	13.4	13.4	13.3	13.3	13.3	13.2	13.2	12.9	12.6	12.2	11.3	10.1	8.49	6.83	5.57	5.04	5.20	6.09
65	0.00	0.00	12.2	12.2	12.3	12.2	12.2	12.2	12.2	12.0	11.6	10.6	9.29	7.66	6.01	4.76	4.20	4.39	5.31
70	0.00	0.00	0.00	10.7	10.7	10.8	10.9	10.8	10.5	10.1	9.80	9.05	7.93	6.54	5.09	3.95	3.36	3.57	4.45
75	0.00	0.00	0.00	0.00	9.08	8.96	8.94	8.82	8.59	8.26	7.96	7.38	6.48	5.34	4.12	3.12	2.52	2.75	3.55
80	0.00	0.00	0.00	0.00	7.15	7.04	7.00	6.88	6.67	6.38	6.10	5.64	4.94	4.07	3.12	2.27	1.68	1.93	2.62
85	0.00	0.00	0.00	0.00	5.29	5.21	5.11	4.96	4.76	4.49	4.22	3.86	3.35	2.75	2.08	1.43	0.85	1.10	1.66
90	0.00	0.00	0.00	0.00	3.51	3.39	3.23	3.04	2.83	2.59	2.33	2.05	1.74	1.40	1.02	0.57	0.01	0.26	0.68
95	0.00	0.00	0.00	0.00	15.7	4.28	2.43	2.35	2.23	2.08	1.90	1.69	1.44	1.17	0.86	0.48	0.02	0.22	0.57
100	0.00	0.00	0.00	0.00	23.9	3.08	1.64	1.67	1.64	1.57	1.46	1.32	1.14	0.94	0.69	0.39	0.02	0.18	0.46
105	0.00	0.00	0.00	0.00	19.3	1.00	0.88	1.00	1.06	1.07	1.03	0.96	0.85	0.70	0.52	0.30	0.03	0.14	0.35
110	0.00	0.00	0.00	9.90	3.31	0.17	0.19	0.39	0.51	0.58	0.61	0.61	0.56	0.47	0.36	0.22	0.04	0.11	0.25
115	0.00	0.00	0.13	0.12	0.13	0.12	0.12	0.12	0.12	0.14	0.22	0.27	0.28	0.25	0.21	0.14	0.05	0.07	0.14
120	0.16	0.15	0.14	0.13	0.12	0.11	0.11	0.11	0.11	0.10	0.10	0.10	0.09	0.08	0.07	0.06	0.06	0.05	0.05
125	0.16	0.15	0.14	0.14	0.13	0.12	0.11	0.10	0.10	0.09	0.09	0.08	0.07	0.07	0.06	0.06	0.05	0.05	0.05
130	0.15	0.15	0.15	0.14	0.13	0.12	0.12	0.11	0.09	0.08	0.08	0.06	0.06	0.05	0.05	0.05	0.05	0.05	0.05
135	0.15	0.15	0.15	0.14	0.13	0.13	0.12	0.11	0.09	0.08	0.07	0.06	0.05	0.04	0.04	0.04	0.04	0.04	0.04
140	0.16	0.15	0.15	0.14	0.13	0.12	0.12	0.11	0.09	0.09	0.08	0.07	0.06	0.05	0.05	0.05	0.05	0.05	0.05
145	0.14	0.13	0.13	0.12	0.12	0.11	0.11	0.10	0.09	0.09	0.08	0.07	0.07	0.06	0.06	0.05	0.05	0.05	0.05
150	0.13	0.13	0.12	0.12	0.11	0.10	0.10	0.09	0.09	0.08	0.08	0.07	0.07	0.06	0.06	0.06	0.06	0.06	0.06
155	0.12	0.11	0.11	0.10	0.09	0.09	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.06	0.07	0.06	0.06	0.06
160	0.10	0.10	0.10	0.09	0.09	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.07	0.07	0.07	0.07
165	0.09	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08
170	0.09	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08
175	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08
180	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks:

## EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

## LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: E41292-BZ	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:171031002
MFR.: Maxim Lighting	SUR.:	PROTECTION ANGLE:

Table--4

UNIT: cd

C(DEG) g (DEG)	285	290	295	300	305	310	315	320	325	330	335	340	345	350	355				
0	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34	9.34				
5	9.24	9.24	9.24	9.24	9.24	9.25	9.26	9.28	9.29	9.30	9.32	9.33	9.35	9.36	9.37				
10	9.14	9.15	9.18	9.21	9.25	9.30	9.35	9.41	9.47	9.53	9.58	9.63	9.67	9.71	9.74				
15	9.06	9.11	9.18	9.26	9.37	9.49	9.62	9.74	9.87	10.00	10.1	10.2	10.3	10.4	10.4				
20	8.86	8.97	9.14	9.33	9.55	9.79	10.0	10.3	10.5	10.7	10.9	11.0	11.2	11.3	11.4				
25	8.67	8.86	9.12	9.43	9.78	10.1	10.5	10.9	11.2	11.5	11.8	12.0	12.2	12.3	12.4				
30	8.50	8.80	9.18	9.64	10.1	10.6	11.1	11.6	12.0	12.4	12.7	13.0	13.2	13.4	13.5				
35	8.25	8.71	9.27	9.90	10.5	11.2	11.8	12.3	12.8	13.2	13.6	13.8	14.1	14.2	14.3				
40	8.01	8.64	9.39	10.2	11.0	11.7	12.4	13.0	13.5	13.9	14.2	14.5	14.6	14.8	14.8				
45	7.82	8.63	9.58	10.5	11.4	12.2	12.9	13.4	13.9	14.2	14.5	14.7	14.9	15.0	15.1				
50	7.67	8.73	9.85	10.9	11.8	12.6	13.2	13.7	14.0	14.3	14.5	14.5	14.6	14.6	14.6				
55	7.58	8.92	10.2	11.3	12.1	12.7	13.3	13.6	13.6	13.7	13.7	13.7	13.7	13.8	13.7				
60	7.54	9.14	10.5	11.5	12.1	12.4	12.7	12.8	12.9	12.8	12.8	12.8	12.8	12.9	12.8				
65	6.76	8.38	9.83	11.0	11.6	11.7	11.8	11.8	11.8	11.8	11.9	11.8	0.00	0.00	0.00				
70	5.72	7.09	8.26	9.17	9.59	9.93	10.3	10.7	10.6	10.5	10.5	0.00	0.00	0.00	0.00				
75	4.59	5.67	6.57	7.24	7.53	7.79	8.07	8.31	8.52	8.84	0.00	0.00	0.00	0.00	0.00				
80	3.39	4.17	4.80	5.25	5.44	5.63	5.82	5.94	6.03	6.26	0.00	0.00	0.00	0.00	0.00				
85	2.15	2.61	2.98	3.23	3.35	3.45	3.55	3.57	3.54	3.58	0.00	0.00	0.00	0.00	0.00				
90	0.88	1.02	1.12	1.20	1.24	1.26	1.27	1.19	1.07	0.89	0.00	0.00	0.00	0.00	0.00				
95	0.73	0.84	0.92	0.98	1.00	1.00	1.00	0.94	9.12	16.6	0.00	0.00	0.00	0.00	0.00				
100	0.59	0.67	0.73	0.76	0.77	0.75	0.73	0.68	8.82	32.8	0.00	0.00	0.00	0.00	0.00				
105	0.44	0.50	0.53	0.54	0.54	0.50	0.47	0.40	2.42	46.3	0.00	0.00	0.00	0.00	0.00				
110	0.30	0.33	0.33	0.33	0.31	0.26	0.20	0.13	0.19	15.0	14.4	0.00	0.00	0.00	0.00				
115	0.16	0.16	0.15	0.13	0.08	0.08	0.09	0.11	0.12	0.23	0.14	0.17	0.00	0.00	0.00				
120	0.05	0.05	0.05	0.07	0.08	0.09	0.09	0.10	0.10	0.12	0.13	0.12	0.15	0.17	0.16				
125	0.05	0.05	0.06	0.07	0.08	0.09	0.10	0.10	0.11	0.11	0.12	0.12	0.13	0.14	0.11				
130	0.04	0.04	0.04	0.07	0.08	0.09	0.09	0.10	0.11	0.11	0.12	0.13	0.13	0.12	0.10				
135	0.04	0.04	0.04	0.06	0.07	0.08	0.08	0.09	0.09	0.11	0.12	0.13	0.13	0.12	0.10				
140	0.05	0.05	0.05	0.05	0.06	0.07	0.07	0.08	0.09	0.11	0.12	0.13	0.12	0.11	0.09				
145	0.05	0.05	0.05	0.06	0.06	0.06	0.07	0.08	0.09	0.11	0.12	0.12	0.11	0.10	0.09				
150	0.06	0.06	0.06	0.06	0.07	0.07	0.07	0.08	0.09	0.10	0.11	0.10	0.10	0.09	0.08				
155	0.07	0.07	0.07	0.07	0.08	0.08	0.08	0.09	0.09	0.09	0.09	0.08	0.08	0.08	0.07				
160	0.07	0.07	0.08	0.08	0.08	0.09	0.09	0.09	0.08	0.08	0.08	0.08	0.08	0.07	0.07				
165	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07				
170	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.07	0.07	0.07	0.07	0.07	0.07	0.07				
175	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08				
180	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08				

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature:30DEG  
Operators:HCZ  
Test Date:2017-10-31

g Range: 0 - 180DEG  
g Interval: 0.5DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.275  
Humidity:65.0%  
Test Distance:6.172m [K=1.0000]  
Remarks: