





PRODUCT DESCRIPTION

*max overall height

A central, cylinder diffuser of opal white acrylic diffuses LED lighting within a cavity of thin ribbed glass of various lengths. Both imaginative and functional, the bright pendants encase an additional down light recessed within a Polished Chrome, Naturally Aged Brass or Matte Black housing casting light downward.

MEASUREMENTS

DIMENSION : 1.5" L x 1.5" W x 10.75" H

MAX OAH : 133.25" OAH

CANOPY : 4.75" W x 1.75" H x 4.75" L

HANGING WEIGHT : 1.98 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 600 Rated (450 Del.)

BULB : 1 x 7.5W LED PCB Integrated, 8W Total

BULB INCLUDED : (Integrated)
DIMMABLE : Universal 3-in-1

CRI : 90 CRI COLOR_TEMP : 3000K

FINISHES OPTION

Black (BK)

Natural Aged Brass (NAB)

Polished Chrome (PC)

GLASS

Clear Ribbed 144

MATERIAL

Steel, Aluminum, Glass

RATINGS

CETLUS

Dry Location



ADDITIONAL

RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER