Quantity:





PRODUCT DESCRIPTION

Soft oval forms offer a modern and playful touch to this LED wall mounted sconce. The face of the fixture is a light guided White acrylic diffuser that even illuminates the edge-lit LED light source. The sleek shape is made even more attractive by the bright illumination provided by the fixture itself. Great for use in bathrooms or corridors, the fixture is ADA compliant and available in 4 lengths. A recessed housing behind the fixture not only mounts the fixture with an attractive extension that makes it appear to be floating off the wall, but it also features a 5-step color temperature select switch allowing you to discreetly adjust the LED lighting to 5 settings ranging from a warmer 2700K to 3000-3500-4000 and daylight white 5000K. These additional product features thereby give more latitude to the design applications without special requests.

MEASUREME	NTS
-----------	-----

BACK PLATE
HANGING WEIGHT

DIMENSION

LAMPING

INPUT VOLTAGE	: 120V	
LUMENS	: 1,500 Rated (1,050 Del.)	
BULB	: 1 x 15W LED AC Intergrated , 15W Total	
BULB INCLUDED	: (Integrated)	
DIMMABLE	: Triac or ELV	
CRI	: 90 CRI	
COLOR_TEMP	: CCT Select 5KK	
LIGHTING_DIRECTION : Backlit		

: 18" W x 5" H x 2.5" Ext

: 4" W x 7.5" H x 9" HCO

: 2.64 lb

FINISHES OPTION



Satin Nickel (SN)

MATERIAL

Aluminum, Polycarbonate

RATINGS

cETLus Damp Location ADA



ADDITIONAL

INSTALL UP/DOWN: Horizontal/Vert RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269 P. 626.956.4200 | F. 626.956.4225 | maximlighting.com