






PRODUCT DESCRIPTION

Channels of Black are fused in an erratic fashion concealing a LED light source that emits a soft and even illumination to the surface below. Light intensity is adjustable down to 10% to allow for multiple room scene settings.



MEASUREMENTS

DIMENSION : 21.25" L x 21.25" W x 8.5" H

MAX OAH : 128.5" OAH

CANOPY : 6.75" W x 1.75" H x 6.75" L

HANGING WEIGHT : 5.28 lb

LAMPING

INPUT VOLTAGE : 120V

LUMENS : 2,500 Rated (1,600 Del.)

BULB : 1 x 36W LED PCB Integrated , 36W Total

BULB INCLUDED : (Integrated)

DIMMABLE : ELV
CRI : 90 CRI
COLOR_TEMP : 3000K

FINISHES OPTION



MATERIAL

Aluminum, Steel

RATINGS

cETLus Dry Location



ADDITIONAL

ADJUSTABLE SLOPE: 70

RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com