






#### PRODUCT DESCRIPTION

Channels of Black are fused in an erratic fashion concealing a LED light source that emits a soft and even illumination to the surface below. Light intensity is adjustable down to 10% to allow for multiple room scene settings.



# **MEASUREMENTS**

DIMENSION : 34.75" L x 33" W x 10.25" H

MAX OAH : 132" OAH

CANOPY : 6" W x 1.5" H x 9.75" L

HANGING WEIGHT : 7.7 lb

## LAMPING

INPUT VOLTAGE : 120V

LUMENS : 3,500 Rated (2,200 Del.)

BULB : 1 x 50W LED PCB Integrated, 50W Total

BULB INCLUDED : (Integrated)

DIMMABLE : ELV
CRI : 80+ CRI
COLOR\_TEMP : 3000K

#### FINISHES OPTION



## MATERIAL

Aluminum, Steel

# **RATINGS**

cETLus Dry Location



#### **ADDITIONAL**

ADJUSTABLE SLOPE: 70 RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

## EASTERN DISTRIBUTION CENTER