ALUMI**LUX** I WALL SCONCE

E41308 | E41328

- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use
- Adjustable plates control beam spread
- Up and down light










E41328 *ADA Version





PRODUCT DESCRIPTION

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.



MEASUREMENT

WEASUKEWENI				
DIMENSION	HCO	HANGING WEIGHT		
4.5"W x 4.5"H x 4.25"EXT	2.25"	2.09 LB		
7"W x 6"H x 2.75"EXT	3.00"	4.84 LB		
	DIMENSION 4.5"W × 4.5"H × 4.25"EXT	DIMENSION HCO 4.5"W x 4.5"H x 4.25"EXT 2.25"		

LAMPING

			TOWEN2	COL		
MODEL	BULB TYPE	CRI	INIT. DEL	TEMP.	DIMMABLE	INPUT
E41308	(2) 3W LED (Integrated)	90+	420 316	3000K	No	120V
*E41328	(2) 3W LED (Integrated)	90+	420 344	3000K	No	120V

LUMENIC COL

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

E41308 Bronze (BZ) Satin Aluminum (SA)

*E41328 White (WT)

Satin Aluminum (SA)

MATERIAL:

Aluminum

AVAILABLE SIZES:

4.5" | 7"

RATINGS:

ETL cETL IP65 Wet Location Title 24 (For Outdoor use) ADA* Option (For E41328)









ADDITIONAL:

RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online INSTALL UP/DOWN: Up

LIGHTING DIRECT: Directional



4200 SHIRLEY DR. I ATLANTA, GA 30336