

ALUMILUX™ I WALL SCONCE

E41530 | E41532 | E41534

- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use
- Dimmable with ELV Dimmer
- Available as: 1-Light, 2-Light, and 3-Light


Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.

SCHEMATIC DIAGRAM



MEASUREMENT

DIMENSIONS : 4.75"W x 4.75"H x 3.5"EXT
 HANGING WEIGHT : 2.2 Lb
 HCO : 2.5"
 BP Width : 4.7"W x 4.7"H

LAMPING

MODEL	BULB TYPE	CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
E41530	(1) 3W PCB LED (Integrated)	90+	210	3000K	ELV	120V
E41532	(2) 3W PCB LED (Integrated)	90+	420	3000K	ELV	120V
E41534	(4) 4W PCB LED (Integrated)	90+	840	3000K	ELV	120V

FINISHES OPTIONS:

Bronze (BZ)



MATERIAL:

Aluminum

AVAILABLE MODELS:

E41530 | E41532 | E41534

RATINGS:

ETL cETL IP65
 Wet Location
 ADA
 Title 24 (For Outdoor use)



ADDITIONAL:

RATED LIFE: 50,000 Hours
 OPERATING TEMP: -20° C (-4°), 40°C (104°F)
 PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336
 P. 626.956.4200 | F. 626.956.4225 | et2online.com