
ALUMI**LUX** I WALL SCONCE

E41540 | E41542 | E41544

- ETL/cETL IP65
- LED 3000K, CRI 90+
- Wet Location
- Title 24 for outdoor use
- Dimmable with ELV Dimmer
- Available as: 1-Light, 2-Light, and 3-Light








PRODUCT DESCRIPTION

Bring the outdoors inside with our line of Architectural high quality interior and exterior wall sconces. European in design and machined out of blocks of solid Aluminum, these sconces have both the look and quality expected for the discriminate buyer. High powered LEDs create dramatic light effects and most are approved for wet location applications.



MEASUREMENT

 DIMENSIONS
 : 4.75"W x 5"H x 1.5"EXT

 HANGING WEIGHT
 : 1.54 Lb

 HCO
 : 2.5"

 BP
 : 3.5"W x 0.4"H

LAMPING

BULB TYPE	CRI	LUMENS	TEMP.	DIMMABLE	INPUT
(1) 4W PCB LED (Integrated)	90+	280	3000K	ELV	120V
(2) 4W PCB LED (Integrated)	90+	560	3000K	ELV	120V
(3) 4W PCB LED (Integrated)	90+	840	3000K	ELV	120V
	(1) 4W PCB LED (Integrated)(2) 4W PCB LED (Integrated)	BULB TYPE CRI (1) 4W PCB LED (Integrated) 90+ (2) 4W PCB LED (Integrated) 90+ (3) 4W PCB LED (Integrated) 90+	(1) 4W PCB LED (Integrated) 90+ 280 (2) 4W PCB LED (Integrated) 90+ 560	(1) 4W PCB LED (Integrated) 90+ 280 3000K (2) 4W PCB LED (Integrated) 90+ 560 3000K	(1) 4W PCB LED (Integrated) 90+ 280 3000K ELV (2) 4W PCB LED (Integrated) 90+ 560 3000K ELV

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

Satin Aluminum (SA) White (WT)



MATERIAL:

Aluminum

AVAILABLE MODELS:

E41540 | E41542 | E41544

RATINGS:

ETL cETL IP65 Wet Location ADA







ADDITIONAL:

RATED LIFE: 50,000 Hours

OPERATING TEMP: -20° C (-4°), 40°C (104°F)

PHOTOMETRIC: Report Found Online



WESTERN DISTRIBUTION CENTER (HEADQUARTERS)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

COL

4200 SHIRLEY DR. I ATLANTA, GA 30336